



NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)

- 1. BRASS
- 2. NICKEL PL. 100 MIN. THICK OVER COPPER PL. 50 MIN. THICK
- 3. THIN GOLD OVER NICKEL PL. 50 MIN. THICK OVER COPPER PL. 50 MIN. THICK
- 4. BERYLLIUM COPPER
- 5. GOLD PL. 3 MIN. THICK OVER NICKEL PL. 50 MIN. THICK OVER COPPER PL. 50 MIN. THICK
- 6. TEFLON

- 1. CRIMPED FERRULE
HEX CRIMP SIZE 5.41mm
- 2. CRIMPED CONTACT PIN
SQ. CRIMP SIZE 1.2mm
- 3. MAX. PANEL THICKNESS=2mm

6	NUT	NOTE 1	NOTE 2	1	NUT-5505-35
5	FERRULE	NOTE 1	NOTE 2	1	FR-53-62-95
4	CONTACT PIN	NOTE 4	NOTE 5	1	300-6421A2-4 -0.7
3	BARREL	NOTE 1	NOTE 2	1	300-6421A2-3 -A2
2	INSULATOR	NOTE 6	NATURAL	1	300-6421A2-2 -75T
1	BODY	NOTE 1	NOTE 3	1	300-6421A2-1
NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.

DIMENSIONS ARE IN MILLIMETERS
UNLESS OTHERWISE SPECIFIED
TOLERANCES
0.5-6 = ±0.2
6-30 = ±0.4
30-120 = ±0.6
120-315 = ±1
315-1000 = ±1.6
1000-2000 = ±2.4

PART NO.	
APPROVED	DATE 07-26-'11
CHECKED	DATE 07-26-'11
DRAWN	DATE 07-26-'11

G.L.I.	
TITLE 1.0/2.3 BULKHEAD CRIMP JACK (FOR FLEX 5 CABLE)	
DRAWING NO. 300-6421A2-A2-75	
FILE NO. R:\D\G\DWG\300\6421A2\A2\75	